

This guide provides general filter replacement direction. Every shower setup may vary. Before beginning, confirm the water is turned off and the area is prepared for a clean replacement. After replacement, slowly restore water flow and check carefully for leaks before regular use.

## 1 Confirm Replacement Parts + Prepare Shower

### Verify required parts:

- S1 replacement cartridge
- Existing S1 Shower Handle Filter

### Prepare:

- Turn off the shower completely
- Confirm the area is dry enough to work safely

**Do not begin replacement if the replacement cartridge is missing, damaged, or incompatible.**

## 2 Open the Shower Handle Filter

### Disassembly:

- Carefully unscrew the S1 shower handle head by rotating it counterclockwise
- Keep the handle steady while removing the head

## 3 Replace the Cartridge

### Cartridge replacement:

- Remove the old cartridge from the shower handle
- Insert the new S1 replacement cartridge into the shower handle

## 4 Reassemble the Shower Handle

### Reassembly:

- Screw the S1 shower handle head back onto the handle
- Turn clockwise until snug (do not overtighten)

## 5 Start-Up + Leak Check

**Start-up:**

- Turn the shower back on
- Allow water to flow through the new cartridge

**Leak check:**

- Check for leaks at the shower handle head
- Confirm everything is functioning properly
- Allow water to run briefly before regular use

---

**Replacement Complete — The cartridge in the S1 Shower Handle Filter has been replaced and is ready to provide fresh filtered water with every shower.**